



Specifications		Standard
Hardware	Dimensions	275*179.2*21.8mm
	Color	Grey
System Platform	Processor	MTK8781, 8-core, 2.2GHZ
	Memory	12GB
	Hard Drive	256GB
	Operating System	Android 13, with GMS
	Battery	24000MAH, 3.8v high voltage lithium battery, 10 hours of battery life (1080P+50% brightness)
	Charging Indicator Light	1: The red light flashes when the battery is \leq 10%, and the red light stays on when the adapter is plugged in for charging 2: The red light stays on for charging with the adapter when the battery is between 10% and 90% 3: The green light stays on for charging with the adapter when the battery is $>$ 90%
	Camera	Front Camera: 5MP fixed-focus camera
		Rear Camera: 13MP autofocus camera 1A True Flash, Flashlight
	2G/3G/4G	GSM: B2/B3/B5/B8 WCDMA: B1/B2/B5/B8 CDMA2000 LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B20/B28A/B28B,B12 /B13/B14/B66/B71 LTE-TDD: B38/B39/B40/B41
	Location	GPS, BeiDou, Galileo, GLONASS
	WIFI	WIFI 802.11(a/b/g/n/ac) frequency 2.4G+5.8G Dual Band WIFI
	Bluetooth	Bluetooth 5.0 (BLE) class1 transmission distance: 10m
Power Supply	WIFI 802.11(a/b/g/n/ac) frequency 2.4G+5.8G Dual Band WIFI	

Display	Resolution	1200*1920, 10.1 inch IPS LCD, 16:10 vertical screen
	Brightness	800cd/m ²
	Touch Screen Stylus Pen	5-point/10-point touch control, optional
	Cover Glass	AG+AF anti-glare coating, hardness 7H
Button	Power Button	*1
	Volume Buttons	*2, Vol+, Vol-
	Custom Button	*1, F key
Sound	Speakers	*2, 1.2W/8Ω aluminum diaphragm speakers, IP67 waterproof
	Earpiece	*1, IP67 waterproof
	Microphone	*1, analog MIC, IP67 waterproof level
Interface	USB *1	Type-C USB2.0 supports OTG
	DC *1	DC 5V/3A
	HDMI	*1, Mini HDMI
	Ethernet Port	*1, RJ45
	Headphone	*1, 3.5mm standard headphone port
	Pogo Pin	*1, 12Pin USB+charging
	SIM Card	*1, standard Micro SIM card slot
TF Card	*1, supports up to 256GB expansion	
Sensor	Gravity Sensor	OK
	Gyro Sensor	OK
	Magnetic Sensor	OK
	Light Sensor	OK
	Distance Sensor	OK
Functional Modules	NFC	13.56MHZ supporting 14443A/14443B/15693 protocols
Reliability	IP Protection Level	IP67 certified
	Drop Resistance	1.2M, on concrete floor
	Operating Temperature	-20°C~60°C
	Storage Temperature	-30°C~70°C
Certification	CE	OK
	RHOS2.0	OK
	IEC62133	OK
	Air and Sea Transport Appraisal	OK
	IP67	OK
	GMS	OK
	MSDS	OK
UN38.3	OK	